

EXTRA-RV



Keyless drill chucks in plastic or metal design with radial locking, for corded and cordless drills, for percussion drilling, with hexagon for assembling and disassembling on the machine spindle.

One-piece design without retaining ring for machines with spindle stop.

Technical features:

- no further locking when drilling and screwing, especially percussion drilling
- very ergonomical, easy to handle, equipped with collision protector
- with carbide inserts in the clamping jaws (size 13)
- for all drills up to 1100 W
- with through-hole for clockwise and anti-clockwise rotation (Thread M 5 or M 6)

Customer advantage:

- with carbide inserts in the clamping jaws
- additional locking no longer necessary (1 movement = 2 functions)

Tool group A01
Type 104-61 **Extra**
with radial locking
metal design



Item no.	Size	Clamping capacity	Mount	Retaining ring	External Ø	Length opened	Length closed	Max. mach. capacity	Through-hole
893350	10	1-10	1/2"-20		42,7	55	60,9	550	•
1033052	10	1-10	1/2"-20	•	42,7	55	60,9	550	
1033053	10	1-10	1/2"-20	•	42,7	55	60,9	550	•
893351	10	1-10	3/8"-24		42,7	55	60,9	550	•
893352	13	1,5-13	1/2"-20		42,7	64,5	72,4	1100	•
802490	13	1,5-13	1/2"-20	•	42,7	64,5	72,4	1100	•
802492	13	1,5-13	1/2"-20	•	42,7	64,5	72,4	1100	•
1033051	13	1,5-13	3/8"-24	•	42,7	64,5	72,4	1100	•

Tool group A01
Type 104-61 **Extra**
with radial locking
plastic design



Item no.	Size	Clamping capacity	Mount	Retaining ring	External Ø	Length opened	Length closed	Max. mach. capacity	Through-hole
767650	10	1-10	1/2"-20		42,7	55	60,9	550	
767651	10	1-10	1/2"-20		42,7	55	60,9	550	•
767638	10	1-10	1/2"-20	•	42,7	55	60,9	550	
767639	10	1-10	1/2"-20	•	42,7	55	60,9	550	•
767573	10	1-10	3/8"-24		42,7	55	60,9	550	•
767649	10	1-10	3/8"-24		42,7	55	60,9	550	
664467	10	1-10	3/8"-24	•	42,7	55	60,9	550	•
767637	10	1-10	3/8"-24	•	42,7	55	60,9	550	
753530	13	1,5-13	1/2"-20		42,7	64,5	72,4	1000	
767580	13	1,5-13	1/2"-20		42,7	64,5	72,4	1000	•
767648	13	1,5-13	1/2"-20	•	42,7	64,5	72,4	1000	
767692	13	1,5-13	1/2"-20	•	42,7	64,5	72,4	1000	•
767640	13	1,5-13	3/8"-24		42,7	64,5	72,4	1000	
767641	13	1,5-13	3/8"-24		42,7	64,5	72,4	1000	•
767647	13	1,5-13	3/8"-24	•	42,7	64,5	72,4	1000	
767657	13	1,5-13	3/8"-24	•	42,7	64,5	72,4	1000	•