



To mount taps.
Suitable for use in conjunction with every of the RÖHM quick-change tapping chucks.

Standard type, without safety clutch

Technical features:

- quick change adaptor without adjustable torque safety clutch
- adjustable in length for presetting outside the machine;
- adjustment by inner hexagon bolt inside the shank of the adaptor
- the selection of the taps results of shank diameter and square
- SE adaptors are mainly used for through-hole or when the depth of the thread is shorter than the core-hole

Tool group A19
Type 358-00 size 0

Item no.	Tap		D	D1	L1	L3	L4	L5	Weight
	Shank-ØY	Square							
389100	2,5	2,1	22	13	15	4	19,5	7	30
389101	2,8	2,1	22	13	15	4	19,5	7	30
389102	3,15	2,5	22	13	15	4	19,5	7	30
389103	3,5	2,7	22	13	15	4	19,5	7	30
389104	3,55	2,8	22	13	15	4	19,5	7	30
389105	4	3	22	13	15	4	19,5	7	30
389106	4	3,15	22	13	15	4	19,5	7	30
389107	4,5	3,4	22	13	15	4	19,5	7	30
389108	5	4	22	13	15	4	19,5	7	30
389109	6	4,9	22	13	15	4	19,5	7	30
389110	6,3	5	22	13	15	4	19,5	7	30
389111	7	5,5	22	13	15	4	19,5	7	30
607828	8	6,2	22	13	15	4	19,5	7	30

Tool group A19
Type 358-01 size 1

Item no.	Tap		D	D1	L1	L3	L4	L5	Weight
	Shank-ØY	Square							
389112	2,5	2,1	30	19	17	4	21,5	7	60
389113	2,8	2,1	30	19	17	4	21,5	7	60
389114	3,15	2,5	30	19	17	4	21,5	7	60
389115	3,5	2,7	30	19	17	4	21,5	7	60
389116	3,55	2,8	30	19	17	4	21,5	7	60
389117	4	3	30	19	17	4	21,5	7	60
389118	4	3,15	30	19	17	4	21,5	7	60
389119	4,5	3,4	30	19	17	4	21,5	7	60
389120	5	4	30	19	17	4	21,5	7	60
389121	6	4,9	30	19	17	4	21,5	7	60
389122	6,3	5	30	19	17	4	21,5	7	60
389123	7	5,5	30	19	17	4	21,5	7	60
389124	8	6,2	30	19	17	4	21,5	7	60
389125	9	7	30	19	17	4	21,5	7	60
389126	10	8	30	19	17	4	21,5	7	60
326616	11	9	30	19	17	4	21,5	7	60
697653	11,2	9	30	19	17	4	21,5	7	60

Tool group A19
Type 358-02 size 2

Item no.	Tap		D	D1	L1	L3	L4	L5	Weight
	Shank-ØY	Square							
389127	6	4,9	48	31	30	5	35	11	250
389128	6,3	5	48	31	30	5	35	11	250
389129	7	5,5	48	31	30	5	35	11	250
389130	8	6,2	48	31	30	5	35	11	250
389131	9	7	48	31	30	5	35	11	250
389132	10	8	48	31	30	5	35	11	250
389133	11	9	48	31	30	5	35	11	250
389134	11,2	9	48	31	30	5	35	11	250
389135	12	9	48	31	30	5	35	11	250
389136	12,5	10	48	31	30	5	35	11	250
389137	14	11	48	31	30	5	35	11	250
389138	14	11,2	48	31	30	5	35	11	250
389139	16	12	48	31	30	5	35	11	250
389140	16	12,5	48	31	30	5	35	11	250
697655	18	14	48	31	30	5	35	11	250
389365	18	14,5	48	31	30	5	35	11	250

Tool group A19
 Type 358-03 size 3

Item no.	Tap		D	D1	L1	L3	L4	L5	Weight
	Shank-ØY	Square							
389141	11	9	70	48	44	6	55,5	14	800
389142	11,2	9	70	48	44	6	55,5	14	800
389143	12	9	70	48	44	6	55,5	14	800
389144	12,5	10	70	48	44	6	55,5	14	800
389145	14	11	70	48	44	6	55,5	14	800
389146	14	11,2	70	48	44	6	55,5	14	800
389147	16	12	70	48	44	6	55,5	14	800
389148	16	12,5	70	48	44	6	55,5	14	800
389149	18	14	70	48	44	6	55,5	14	800
389150	18	14,5	70	48	44	6	55,5	14	800
389151	20	16	70	48	44	6	55,5	14	800
389152	22	18	70	48	44	6	55,5	14	800
389153	22,4	18	70	48	44	6	55,5	14	800
389154	25	20	70	48	44	6	55,5	14	800
600282	28	22	70	48	44	6	55,5	14	800

 Tool group A19
 Type 358-04 size 4

Item no.	Tap		D	D1	L1	L3	L4	L5	Weight
	Shank-ØY	Square							
389155	18	14	90	60	71	13	63	42	1500
389156	18	14,5	90	60	71	13	63	42	1500
389157	20	16	90	60	71	13	63	42	1500
389158	22	18	90	60	71	13	63	42	1500
389159	22,4	18	90	60	71	13	63	42	1500
389160	25	20	90	60	71	13	63	42	1500
389161	28	22	90	60	71	13	63	42	1500
389162	32	24	90	60	71	13	63	42	1500
389163	36	29	90	60	71	13	63	42	1500

 Tool group A19
 Type 358-07 size 7

Item no.	Tap		D	D1	L1	L3	L4	L5	Weight
	Shank-ØY	Square							
389804	4,5	3,4	40	26	30	5	32	13	120
389805	5	4	40	26	30	5	32	13	120
389806	6	4,9	40	26	30	5	32	13	120
389807	6,3	5	40	26	30	5	32	13	120
389808	7	5,5	40	26	30	5	32	13	120
389809	8	6,2	40	26	30	5	32	13	120
389810	9	7	40	26	30	5	32	13	120
389811	10	8	40	26	30	5	32	13	120
389812	11	9	40	26	30	5	32	13	120
389813	11,2	9	40	26	30	5	32	13	120
389814	12	9	40	26	30	5	32	13	120
389815	12,5	10	40	26	30	5	32	13	120
389816	14	11	40	26	30	5	32	13	120
697656	14	11,2	40	26	30	5	32	13	120