



To mount taps.
Suitable for use in conjunction with every of the RÖHM quick-change tapping chucks.

With safety clutch for torque setting, torque adjustment for marked thread

Technical features:

- quick change adaptors with adjustable torque safety clutch
- adjustable in length for presetting outside the machine;
- adjustment by inner hexagon bolt inside the shank of the adaptor
- adaptors must be selected to suit the shank diameter and square of the tap, each adaptor can only be used for one shank diameter
- SES adaptors with safety clutch for limitation of the torque are mainly used for blind hole tapping or in material with high strength
- all adaptors are factory set by us for a torque corresponding to a specific cutting force of $K_c=2500 \text{ N/mm}^2$ which allows 100% for progressive dulling of the tool cutting edges

Tool group A19
Type 358-50 size 0

Item no.	Tap			D	D1	L1	L3	L4	L5	Weight
	Thread	Shank-ØY	Square							
389230	M1,6	2,5	2,1	24	13	15	20	19,5	21	60
704380	M3	2,5	2,1	24	13	15	20	19,5	21	60
389231	M2,5	2,8	2,1	24	13	15	20	19,5	21	60
704381	M4	2,8	2,1	24	13	15	20	19,5	21	60
389232	M4	3,15	2,5	24	13	15	20	19,5	21	60
389233	M3	3,5	2,7	24	13	15	20	19,5	21	60
704382	M5	3,5	2,7	24	13	15	20	19,5	21	60
389234	M4	3,55	2,8	24	13	15	20	19,5	21	60
389235	M3,5	4	3	24	13	15	20	19,5	21	60
389236	M5	4	3,15	24	13	15	20	19,5	21	60
389237	M4	4,5	3,4	24	13	15	20	19,5	21	60
704383	M6	4,5	3,4	24	13	15	20	19,5	21	60
389238	M5	5	4	24	13	15	20	19,5	21	60
690595	M5	6	4,9	24	13	15	20	19,5	21	60
389239	M6	6	4,9	24	13	15	20	19,5	21	60
690596	M8	6	4,9	24	13	15	20	19,5	21	60
389240	M6	6,3	5	24	13	15	20	19,5	21	60
690597	M8	6,3	5	24	13	15	20	19,5	21	60
389241	M10	7	5,5	24	13	15	20	19,5	21	60
690598	M8	8	6,2	24	13	15	20	19,5	21	60
389242	M10	8	6,2	24	13	15	20	19,5	21	60

Tool group A19
Type 358-51 size 1

Item no.	Tap			D	D1	L1	L3	L4	L5	Weight
	Thread	Shank-ØY	Square							
389243	M1,6	2,5	2,1	32,5	19	17	25	21,5	26	150
697639	M3	2,5	2,1	32,5	19	17	25	21,5	26	150
389244	M2,5	2,8	2,1	32,5	19	17	25	21,5	26	150
697640	M4	2,8	2,1	32,5	19	17	25	21,5	26	150
389245	M4	3,15	2,5	32,5	19	17	25	21,5	26	150
389246	M3	3,5	2,7	32,5	19	17	25	21,5	26	150
697641	M5	3,5	2,7	32,5	19	17	25	21,5	26	150
389247	M4	3,55	2,8	32,5	19	17	25	21,5	26	150
389248	M3,5	4	3	32,5	19	17	25	21,5	26	150
389249	M5	4	3,15	32,5	19	17	25	21,5	26	150
389250	M4	4,5	3,4	32,5	19	17	25	21,5	26	150
697642	M6	4,5	3,4	32,5	19	17	25	21,5	26	150
389251	M5	5	4	32,5	19	17	25	21,5	26	150
668272	M5	6	4,9	32,5	19	17	25	21,5	26	150
668273	M6	6	4,9	32,5	19	17	25	21,5	26	150
389252	M8	6	4,9	32,5	19	17	25	21,5	26	150
668274	M6	6,3	5	32,5	19	17	25	21,5	26	150
389253	M8	6,3	5	32,5	19	17	25	21,5	26	150
389254	M10	7	5,5	32,5	19	17	25	21,5	26	150
668275	M8	8	6,2	32,5	19	17	25	21,5	26	150
389255	M10	8	6,2	32,5	19	17	25	21,5	26	150
389256	M12	9	7	32,5	19	17	25	21,5	26	150
389257	M10	10	8	32,5	19	17	25	21,5	26	150
389258	M14	11	9	32,5	19	17	25	21,5	26	150
697643	M14	11,2	9	32,5	19	17	25	21,5	26	150

Tool group A19
 Type 358-52 **size 2**

Item no.	Tap			D	D1	L1	L3	L4	L5	Weight
	Thread	Shank-ØY	Square							
389259	M5	6	4,9	50,5	31	30	31	35	34	550
668277	M6	6	4,9	50,5	31	30	31	35	34	550
668278	M8	6	4,9	50,5	31	30	31	35	34	550
690599	M6	6,3	5	50,5	31	30	31	35	34	550
389260	M8	6,3	5	50,5	31	30	31	35	34	550
389261	M10	7	5,5	50,5	31	30	31	35	34	550
690600	M8	8	6,2	50,5	31	30	31	35	34	550
389262	M10	8	6,2	50,5	31	30	31	35	34	550
389263	M12	9	7	50,5	31	30	31	35	34	550
389264	M10	10	8	50,5	31	30	31	35	34	550
389265	M14	11	9	50,5	31	30	31	35	34	550
389266	M14	11,2	9	50,5	31	30	31	35	34	550
389267	M16	12	9	50,5	31	30	31	35	34	550
389268	M16	12,5	10	50,5	31	30	31	35	34	550
389269	M18	14	11	50,5	31	30	31	35	34	550
389270	M18	14	11,2	50,5	31	30	31	35	34	550
704407	M20	14	11,2	50,5	31	30	31	35	34	550
389271	M20	16	12	50,5	31	30	31	35	34	550
389272	M22	16	12,5	50,5	31	30	31	35	34	550
707942	M24	18	14	50,5	31	30	31	35	34	550
389273	M22	18	14,5	50,5	31	30	31	35	34	550

 Tool group A19
 Type 358-53 **size 3**

Item no.	Tap			D	D1	L1	L3	L4	L5	Weight
	Thread	Shank-ØY	Square							
389274	M14	11	9	72	48	44	41	55,5	45	1700
389275	M14	11,2	9	72	48	44	41	55,5	45	1700
389276	M16	12	9	72	48	44	41	55,5	45	1700
389277	M16	12,5	10	72	48	44	41	55,5	45	1700
389278	M18	14	11	72	48	44	41	55,5	45	1700
389279	M18	14	11,2	72	48	44	41	55,5	45	1700
704410	M20	14	11,2	72	48	44	41	55,5	45	1700
389280	M20	16	12	72	48	44	41	55,5	45	1700
389281	M22	16	12,5	72	48	44	41	55,5	45	1700
389282	M24	18	14	72	48	44	41	55,5	45	1700
389283	M22	18	14,5	72	48	44	41	55,5	45	1700
704411	M24	18	14,5	72	48	44	41	55,5	45	1700
704412	M27	20	16	72	48	44	41	55,5	45	1700
389284	M30	20	16	72	48	44	41	55,5	45	1700
389285	M30	22	18	72	48	44	41	55,5	45	1700
389286	M33	22,4	18	72	48	44	41	55,5	45	1700
389287	M33	25	20	72	48	44	41	55,5	45	1700
704409	M36	28	22	72	48	44	41	55,5	45	1700
389288	M38	28	22	72	48	44	41	55,5	45	1700

 Tool group A19
 Type 358-54 **size 4**

Item no.	Tap			D	D1	L1	L3	L4	L5	Weight
	Thread	Shank-ØY	Square							
389289	M24	18	14	95	60	71	61	63	68	3300
389290	M22	18	14,5	95	60	71	61	63	68	3300
697645	M24	18	14,5	95	60	71	61	63	68	3300
704390	M27	20	16	95	60	71	61	63	68	3300
389291	M30	20	16	95	60	71	61	63	68	3300
389292	M30	22	18	95	60	71	61	63	68	3300
389293	M33	22,4	18	95	60	71	61	63	68	3300
704391	M33	25	20	95	60	71	61	63	68	3300
389294	M36	28	22	95	60	71	61	63	68	3300
389295	M38	28	22	95	60	71	61	63	68	3300
389296	M39	32	24	95	60	71	61	63	68	3300
697646	M42	32	24	95	60	71	61	63	68	3300
389297	M45	36	29	95	60	71	61	63	68	3300
697647	M48	36	29	95	60	71	61	63	68	3300

Tool group A19
 Type 358-57 size 7

Item no.	Tap			D	D1	L1	L3	L4	L5	Weight
	Thread	Shank-ØY	Square							
329468	M4	4,5	3,4	40,5	26	30	27	32	30	300
704384	M6	4,5	3,4	40,5	26	30	27	32	30	300
329469	M5	5	4	40,5	26	30	27	32	30	300
690602	M5	6	4,9	40,5	26	30	27	32	30	300
329470	M6	6	4,9	40,5	26	30	27	32	30	300
690603	M8	6	4,9	40,5	26	30	27	32	30	300
690604	M6	6,3	5	40,5	26	30	27	32	30	300
332136	M8	6,3	5	40,5	26	30	27	32	30	300
332137	M10	7	5,5	40,5	26	30	27	32	30	300
690605	M8	8	6,2	40,5	26	30	27	32	30	300
332138	M10	8	6,2	40,5	26	30	27	32	30	300
332139	M12	9	7	40,5	26	30	27	32	30	300
332140	M10	10	8	40,5	26	30	27	32	30	300
332141	M14	11	9	40,5	26	30	27	32	30	300
332142	M14	11,2	9	40,5	26	30	27	32	30	300
332143	M16	12	9	40,5	26	30	27	32	30	300
332144	M16	12,5	10	40,5	26	30	27	32	30	300
332145	M18	14	11	40,5	26	30	27	32	30	300