



To mount taps.
Suitable for use in conjunction with every of the RÖHM quick-change tapping chucks.

With safety clutch for torque setting and length adjustment for taps

Technical features:

- quick change adaptors with adjustable torque safety clutch
- adjustable in length for presetting outside the machine;
- adjustment by inner hexagon bolt inside the shank of the adaptor
- adaptors must be selected to suit the shank diameter and square of the tap, each adaptor can only be used for one shank diameter
- SESN adaptors with safety clutch for limitation of the torque are mainly used for blind hole tapping or in material with high strength
- all adaptors are factory set by us for a torque corresponding to a specific cutting force of $K_c=2500 \text{ N/mm}^2$ which allows 100% for progressive dulling of the tool cutting edges

Tool group A19
Type 358-61 size 1

Item no.	Tap			D	D1	L1	L4	L5	Adjusting range	Weight
	Thread	Shank-ØY	Square							
389310	M1,6	2,5	2,1	32,5	19	17	21,5	33	10	170
704418	M3	2,5	2,1	32,5	19	17	21,5	33	10	170
389311	M2,5	2,8	2,1	32,5	19	17	21,5	33	10	170
704419	M4	2,8	2,1	32,5	19	17	21,5	33	10	170
389312	M4	3,15	2,5	32,5	19	17	21,5	33	10	170
389313	M3	3,5	2,7	32,5	19	17	21,5	33	10	170
704420	M5	3,5	2,7	32,5	19	17	21,5	33	10	170
389314	M4	3,55	2,8	32,5	19	17	21,5	33	10	170
389315	M3,5	4	3	32,5	19	17	21,5	33	10	170
389316	M5	4	3,15	32,5	19	17	21,5	33	10	170
389317	M4	4,5	3,4	32,5	19	17	21,5	33	10	170
734456	M6	4,5	3,4	32,5	19	17	21,5	33	10	170
389318	M5	5	4	32,5	19	17	21,5	33	10	170
690618	M5	6	4,9	32,5	19	17	21,5	33	10	170
690619	M6	6	4,9	32,5	19	17	21,5	33	10	170
389319	M8	6	4,9	32,5	19	17	21,5	33	10	170
694838	M6	6,3	5	32,5	19	17	21,5	33	10	170
389320	M8	6,3	5	32,5	19	17	21,5	33	10	170
389321	M10	7	5,5	32,5	19	17	21,5	33	10	170
694839	M8	8	6,2	32,5	19	17	21,5	33	10	170
389322	M10	8	6,2	32,5	19	17	21,5	33	10	170
389323	M12	9	7	32,5	19	17	21,5	33	10	170
389324	M10	10	8	32,5	19	17	21,5	33	10	170
389325	M14	11	9	32,5	19	17	21,5	33	10	170
704421	M24	11,2	9	32,5	19	17	21,5	33	10	170

Tool group A19
Type 358-62 size 2

Item no.	Tap			D	D1	L1	L4	L5	Adjusting range	Weight
	Thread	Shank-ØY	Square							
389326	M5	6	4,9	50,5	31	30	35	59	15	700
690621	M6	6	4,9	50,5	31	30	35	59	15	700
690622	M8	6	4,9	50,5	31	30	35	59	15	700
690623	M6	6,3	5	50,5	31	30	35	59	15	700
389327	M8	6,3	5	50,5	31	30	35	59	15	700
389328	M10	7	5,5	50,5	31	30	35	59	15	700
690624	M8	8	6,2	50,5	31	30	35	59	15	700
389329	M10	8	6,2	50,5	31	30	35	59	15	700
389330	M12	9	7	50,5	31	30	35	59	15	700
389331	M10	10	8	50,5	31	30	35	59	15	700
389332	M14	11	9	50,5	31	30	35	59	15	700
389333	M14	11,2	9	50,5	31	30	35	59	15	700
389334	M16	12	9	50,5	31	30	35	59	15	700
389335	M16	12,5	10	50,5	31	30	35	59	15	700
389336	M18	14	11	50,5	31	30	35	59	15	700
389337	M18	14	11,2	50,5	31	30	35	59	15	700
704423	M20	14	11,2	50,5	31	30	35	59	15	700
389338	M20	16	12	50,5	31	30	35	59	15	700
389339	M22	16	12,5	50,5	31	30	35	59	15	700
704424	M24	18	14	50,5	31	30	35	59	15	700
369406	M22	18	14,5	50,5	31	30	35	59	15	700
704425	M24	18	14,5	50,5	31	30	35	59	15	700

further sizes on request