



PZS



Used on grinding, milling and engraving machines, jig boring machines, for measurement and inspection work.



Simple clamping and releasing with the inner hexagon key. Clamping jaws adjustable in steps, lock in automatically.

Technical features:

- with draw-down effect
- made out of alloyed tool steel, hardened and precision ground on all sides
- horizontal ground prism for PL-S micro size 2
- no spindle which, for example, could become clogged during erosion

Tool group A29
Type 735-60 **PL-S micro**
with quick adjustment

Item no.	Size	Square-ness	Parallelism	Jaw width	B	C	Length body	G	H	J	Weight kg
370773	1	0,005	0,002	34	25	15	75	20	20	25	0,35
370774	2	0,005	0,002	45	50	20	110	25	25	35	1



Used on grinding, milling and engraving machines, jig boring machines, for measurement and inspection work.



Simple clamping and releasing with the inner hexagon key. Clamping jaws adjustable in steps, lock in automatically.

Technical features:

- with draw-down effect
- made out of alloyed tool steel, hardened and precision ground on all sides
- horizontal and vertical ground prism for PL-S size 1 and 2, horizontal ground prism for PL-S size 3
- no spindle which, for example, could become clogged during erosion

Tool group A29
Type 735-65 **PL-S**
with quick adjustment

Item no.	Size	Square-ness	Parallelism	Jaw width	B	C	Length body	G	H	J	Weight kg
370775	1	0,005	0,002	70	80	30	160	32	33	45	3
370776	2	0,005	0,002	90	120	40	210	40	40	50	5,8
370777	3	0,005	0,002	120	150	40	280	50	60	70	13,5



Used on grinding, milling and engraving machines, jig boring machines, for measurement and inspection work.

Clamping and releasing with locking screws on the top side. Clamping jaws adjustable in steps, lock in automatically.

Technical features:

- with draw-down effect
- made out of alloyed tool steel, hardened and precision ground on all sides
- horizontal and vertical ground prism for PLF
- no spindle which, for example, could become clogged during erosion

Tool group A29
Type 735-70 **PLF**
with quick adjustment in accuracy to gauge

Item no.	Size	Squareness	Parallelism	Jaw width	B	C	Length body	Weight kg
1111185	0	0,005	0,005	50	65	25	140	1,4
1111186	1	0,005	0,005	73	100	35	190	4,1
1111187	2	0,005	0,005	100	125	45	245	7,3